

# **OSBORN** SAFETY DATA SHEET

Date Issued- 6/1/2015 SDS no. BA729/2

## **1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT DESCRIPTION CHEMICAL NAME	339E Blended abrasive solid
GENERAL USE MANUFACTURER ADDRESS	Polish for metal finishing Osborn 3440 Symmes Rd. Hamilton OH 45015 USA
CONTACT NUMBER	1-513-860-3400
EMERGENCY CONTACT	PLANT OPERATIONS
EMERGENCY PHONE	1-513-678-3672
24 HOUR EMERGENCY	
TELEPHONE NUMBER	CHEMTREC (24 HOURS) 800-424-9300
2. HAZARD IDENTIFICATION	

#### **EMERGENCY OVERVIEW**

Fatty Acid /Glyceride

CAUTION! May cause eye or skin irritation. Proper protective			
equipment should be worn. Wash skin after use.			
May cause	eye irritation		
May cause	mild skin irritation		
Large oral	doses may cause irritation		
Avoid brea	thing dust when used in a bu	uffing process	
None expe	cted		
Avoid breathing dust from buffing operations			
Wash thoroughly after handling			
Wear portective gloves/protective clothing/eye protection/ face protection			
If on Skin: Wash with soap and water			
If in eyes: Wash cautiously with water for 15 minutes.			
3. COMPOSITION/INGREDIENT INFORMATION			
CAS	PEL/ TLV	Weight %	
1344-28-1	10 mg/ M3	65-80%	
	equipment May cause May cause Large oral of Avoid brea None expe Avoid brea Wash thore Wear porte If on Skin: V If in eyes: V DIENT INFO	equipment should be worn. Wash skin May cause eye irritation May cause mild skin irritation Large oral doses may cause irritation Avoid breathing dust when used in a bu None expected Avoid breathing dust from buffing oper Wash thoroughly after handling Wear portective gloves/protective clot If on Skin: Wash with soap and water If in eyes: Wash cautiously with water for	equipment should be worn. Wash skin after use.   May cause eye irritation   May cause mild skin irritation   Large oral doses may cause irritation   Avoid breathing dust when used in a buffing process   None expected   Avoid breathing dust from buffing operations   Wash thoroughly after handling   Wear portective gloves/protective clothing/eye prot   If on Skin: Wash with soap and water   If in eyes: Wash cautiously with water for 15 minutes   DIENT INFORMATION   CAS PEL/TLV   Weight %

Not Hazardous

18-24%

Petroleum Oil or Wax	Not Hazardous	2-6%

4. FIRST AID MEASUR	ES
Inhalation	If exposed to excessive levels of dust, remove to fresh air.
	Get medical attention if cough, irritation or other symptoms develop.
Skin Contact	Wash with soap and water.
	Get medical attention if irritation or rash develop.
Eye Contact	Immediately flush eyes with plenty of water for 15 minutes.
	If abrasive particles are not removed, obtain medical attention.
Ingestion	Swallowing less than an ounce will not cause significant harm.
	For larger amounts do not induce vomiting,
	but give two 12 ounce glasses of water and obtain medical advice.
5. FIRE FIGHTING MEA	ASURES
Flash Point	>350 F
Extinguishing Media	Use alcohol foam, carbon dioxide, or dry chemical
	when fighting fires involving this material.
Fire fighting Procedure	Remove ignition source and fight fire as if it were a grease fire.

	nemove ignition source and right me as in it were a grease me.
Special Protective Equipment	As in any fire, wear self contained breathing apparatus (pressure-demand,
	MSHA/NIOSH approved or equivalent) and full protective gear.
Hazardous Combustion	If heated to high temperature the product may emit carbon monoxide
Products	and carbon dioxide

#### **6 ACCIDENTAL RELEASE MEASURES**

Environmental Precautons

None known

Methods for Clean upSweep or Scoop up material for reuse or reclaim if possible,<br/>otherwise place in a disposal container for proper disposition.

7. HANDLING AND STORAGE		
Handling	No special handling requirements are known	
Storage	Keep out of sun and away from heat sources, as product may melt. Observe all safeguards for container residue until cleaned or destroyed. Do not flush to sewers or waterways unless authorized to do so by appropriate government official.	

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

	LINGOIN			
Exposure Limit Values	10 mg/ m3 as dust			
Engineering Measures	Ventilatior	n to keep dust level at exp	osure limits	
Hygiene Measures				
Respiratory Protection	Wear a dust mask			
Hand Protection	Wear gloves			
Eye Protection	Wear safety glasses with side shields or goggles			
Skin Protection	Wash with soap and water before eating or after shift			
9. PHYSICAL AND CHEMICAL PROPERTIES				
Physical State	Solid	Solubility in Water	None	
Color	White Elach Point >250E			

i nysicai state	00110		none
Color	White	Flash Point	>350F
Boiling Point	N/A	Vapor Density	N/A
Melting Point	135 F	<b>Evaporation Rate</b>	N/A
Specific Gravity	> 1.3	Odor	Mild;
рН	N/A	VOC	None
Autoignition Temperature	N/A		

#### **10. STABILITY AND REACTIVITY**

Stability	Product is stable	
Conditions to Avoid	Material can ignite if exposed to a continuous flame	or heat source
Incompatible Materials	None known	
Hazardous Decomposition Products	If product is involved in a fire, carbon monoxide cou	d be emitted
Hazardous Polymerization	Will Not occur	

### **11. TOXICOLOGICAL INFORMATION**

Eyes	May cause irritation from abrasion.
Skin Contact	May cause irritation
Skin Absorption	Not likely
Inhalation	Dust form buffing operation may cause irritation
Swallowing	No adverse effect is expected
<b>12. ECOLOGICAL INFORMA</b>	ATION
Ecological Information	No data available

Bioaccumulative Potential Bioaccumulation is unlikey

**Comments** This product is not believed to be toxic to aquatic life.

# **13. DISPOSAL CONSIDERATIONS**

General	If discarded, the material in its original unused form is not a RCRA hazardous waste.
	Disposal should be in accordance with State and Local regulations for the
	disposal of non-hazardous waste. Be sure to check if compound (after used)
	has come in contact with a hazardous substance before disposal

Packaging Dispose in clean receptical or box.

14. TRANSPORTATION	INFORMATION
DOT	Not regulated
Classifica	-
IMDG Classification	Not regulated
ICAO Classification	Not regulated
15. REGULATORY INFO	RMATION
UNITED STATES	
Sara Title III	
313 Reportable Ingredie	ents None
302/304 Emergency Plan	ning
Emergency I	Plan
CERCLA	oonse, Compensation and Liabiity Act) RQ None
EPA HAZARD CATEGORIES	
	312 - None
TSCA (Toxic Substance Contr	-
	atus - All ingredients are on the TSCA list
16. OTHER INFORMATI	
Revision Number	BA729-5
Supersedes Date	1/1/2014
HMIS Rating	1-1-0-0
Manufacturer Disclaimer	Metal Dusts from the buffing of brass, zinc and especially magnesium or aluminum
	along with buffing cloth fibers and compound residues may cause fires or explosions
	when exposed to a strong ignition source. These fires typically are started in the vent
	pipes, collector bags or receptacles used in waste gathering from the buffing
	ventilation system. Make sure that the collectors are changed frequently and the
	waste kept in a cool, dry environment that is free from sparks or other strong ignition
	sources. The collection devices should be grounded to minimize static charges.Dust
	collection receptacles should be designed by engineers who are familiar with the
	potential hazard of a flammable or explosive dust. If such a fire occurs, fight the fire
	with a Class D fire extinguisher. Do not use water or a halogenated extinguishing media.