



# SAFETY DATA SHEET

Date Issued- 8/20/18

SDS no. BA-529

## 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT DESCRIPTION** 3562  
**CHEMICAL NAME** Blended abrasive solid  
  
**GENERAL USE** Polish for metal finishing  
**MANUFACTURER ADDRESS** Osborn  
3440 Symmes Rd. Hamilton  
OH 45015 USA  
**CONTACT NUMBER** 1-513-860-3400  
**EMERGENCY CONTACT** PLANT OPERATIONS  
**EMERGENCY PHONE** 1-513-678-3672  
**24 HOUR EMERGENCY**  
**TELEPHONE NUMBER** CHEMTREC (24 HOURS) 800-424-9300

## 2. HAZARD IDENTIFICATION

### EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS** CAUTION! May cause eye or skin irritation. Proper protective equipment should be worn. Wash skin after use.

### POTENTIAL HEALTH EFFECTS

Eye May cause eye irritation  
Skin May cause mild skin irritation  
Ingestion Large oral doses may cause irritation  
Inhalation Product as supplied is not hazardous. May cause serious health damage due to breathing dust from buffing operation with this material  
Chronic Cancer

### GHS Label requirements

Pictogram --



Signal Word--- WARNING

### Hazard Statement

Carc. 2 H351 Suspected of causing cancer.

### Precautionary Statements

P260 Do not breathe dusts from buffing operation with this material  
P285 In case of inadequate ventilation, wear respiratory protection  
P280 Wear protective gloves/protective clothing/eye protection/ face protection  
P302+P352 If on Skin: Wash with soap and water  
P305+P351 If in eyes: Wash cautiously with water for 15 minutes.

## 3. COMPOSITION/INGREDIENT INFORMATION

Ingredients	CAS	TLV; PEL	Weight %
Aluminum Oxide	1344-28-1	10 mg/M3	60-90%
Fatty Acid /Glyceride		Not Hazardous	10-15%
Petroleum Wax or Oil		Not Hazardous	3-10%

#### 4. FIRST AID MEASURES

<b>Inhalation</b>	If exposed to excessive levels of dust, remove to fresh air. Get medical attention if cough, irritation or other symptoms develop.
<b>Skin Contact</b>	Wash with soap and water. Get medical attention if irritation or rash develop.
<b>Eye Contact</b>	Immediately flush eyes with plenty of water for 15 minutes. If abrasive particles are not removed, obtain medical attention.
<b>Ingestion</b>	Swallowing less than an ounce will not cause significant harm. For larger amounts do not induce vomiting, but give two 12 ounce glasses of water and obtain medical advice.

#### 5. FIRE FIGHTING MEASURES

<b>Flash Point</b>	>350 F
<b>Extinguishing Media</b>	Use alcohol foam, carbon dioxide, or dry chemical when fighting fires involving this material.
<b>Fire fighting Procedure</b>	Remove ignition source and fight fire as if it were a grease fire.
<b>Special Protective Equipment</b>	As in any fire, wear self contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.
<b>Hazardous Combustion Products</b>	If heated to high temperature the product may emit carbon monoxide and carbon dioxide

#### 6 ACCIDENTAL RELEASE MEASURES

**Environmental Precautions** None known

**Methods for Clean up** Sweep or Scoop up material for reuse or reclaim if possible, otherwise place in a disposal container for proper disposition.

#### 7. HANDLING AND STORAGE

**Handling** No special handling requirements are known

**Storage** Keep out of sun and away from heat sources, as product may melt.  
Observe all safeguards for container residue until cleaned or destroyed.  
Do not flush to sewers or waterways unless authorized to do so by appropriate government official.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limit Values	10 mg/ m3 as dust
Engineering Measures	Ventilation to keep dust level at exposure limits
Hygiene Measures	
Respiratory Protection	Wear a dust mask
Hand Protection	Wear gloves
Eye Protection	Wear safety glasses with side shields or goggles
Skin Protection	Wash with soap and water before eating or after shift

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Solid	Solubility in Water	None
Color	Brown	Flash Point	>350F
Boiling Point	N/A	Vapor Density	N/A
Melting Point	135 F	Evaporation Rate	N/A
Specific Gravity	> 1.3	Odor	Mild;
pH	N/A		
Autoignition Temperature	N/A		

## 10. STABILITY AND REACTIVITY

Stability	Product is stable
Conditions to Avoid	Material can ignite if exposed to a continuous flame or heat source
Incompatible Materials	None known
Hazardous Decomposition Products	If product is involved in a fire, carbon monoxide could be emitted
Hazardous Polymerization	Will Not occur

## 11. TOXICOLOGICAL INFORMATION

Eyes	May cause irritation from abrasion.
Skin Contact	May cause irritation
Skin Absorption	Not likely
Inhalation	Dust form buffing operation may cause irritation
Swallowing	

## 12. ECOLOGICAL INFORMATION

Ecological Information	No data available
Bioaccumulative Potential	Bioaccumulation is unlikely

**Comments**

This product is not believed to be toxic to aquatic life.

**13. DISPOSAL CONSIDERATIONS**

<b>General</b>	If discarded, the material in its original unused form is not a RCRA hazardous waste. Disposal should be in accordance with State and Local regulations for the disposal of non-hazardous waste. Be sure to check if compound (after used) has come in contact with a hazardous substance before disposal
<b>Packaging</b>	Dispose in clean receptical or box.

**14. TRANSPORTATION INFORMATION**

<b>DOT</b>	Not regulated
<b>IMDG Classification</b>	Not regulated
<b>ICAO Classification</b>	Not regulated

**15. REGULATORY INFORMATION****UNITED STATES****Sara Title III**

313 Reportable Ingredients - 1344-28-1 aluminum oxide  
302/304 Emergency Planning  
Emergency Plan

**California Prop 65-**

**WARNING: This product contains a chemical known to the State of California to cause cancer and/or reproductive harm.**

<u>Ingredient</u>	<u>Cancer</u>	<u>Reproductive</u>
Titanium Dioxide	Yes	No

**CERCLA (Comprehensive Response, Compensation and Liability Act)**

**CERCLA RQ** - None

**EPA HAZARD CATEGORIES**

SARA 311/312 - None

**TSCA (Toxic Substance Control Act)**

TSCA Status - All ingredients are on the TSCA list

**16. OTHER INFORMATION**

<b>Revision Number</b>	BA-529-5
<b>Supersedes Date</b>	1/1/2014
<b>HMIS Rating</b>	1-1-0-0

**Manufacturer Disclaimer**

Metal Dusts from the buffing of brass, zinc and especially magnesium or aluminum along with buffing cloth fibers and compound residues may cause fires or explosions when exposed to a strong ignition source. These fires typically are started in the vent pipes, collector bags or receptacles used in waste gathering from the buffing

ventilation system. Make sure that the collectors are changed frequently and the waste kept in a cool, dry environment that is free from sparks or other strong ignition sources. The collection devices should be grounded to minimize static charges. Dust collection receptacles should be designed by engineers who are familiar with the potential hazard of a flammable or explosive dust. If such a fire occurs, fight the fire with a Class D fire extinguisher. Do not use water or a halogenated extinguishing media.