



# OSBORN SILICONE 76241

## SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

#### Product identifier

Chemical Name	Mixture
CAS No.	Mixture
Trade Name	OSBORN SILICONE 76241
Product Code	M-5825

#### Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Lubricant
Uses Advised Against	None
Company Identification	Osborn 2350 Salisbury Road North Richmond, IN 47374 USA

Telephone	(765) 965-5333
Fax	(765) 935-0212
E-Mail (competent person)	<a href="mailto:marketsupport@osborn.com">marketsupport@osborn.com</a>

#### Emergency telephone number

Emergency Phone No.	<b>Transportation Emergency:</b> CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)
---------------------	---

### SECTION 2: HAZARDS IDENTIFICATION

#### Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; Repr. 2; STOT SE 3; STOT RE 2; Asp. Tox. 1

#### Label elements

Hazard Symbol



Signal word(s)

**DANGER**

Hazard Statement(s)

Extremely flammable aerosol.  
Contains gas under pressure; may explode if heated.  
Causes skin irritation.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs through prolonged or repeated exposure: Central Nervous System, Route: Inhalation  
May cause drowsiness or dizziness.  
May be fatal if swallowed and enters airways.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Do not spray on an open flame or other ignition source.  
Do not pierce or burn, even after use.  
Use only outdoors or in a well-ventilated area.

Precautionary Statement(s)



# OSBORN SILICONE 76241

Do not breathe mist/vapours/spray.

Wear protective gloves/eye protection.

Wash hands and exposed skin after use.

Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

**Other hazards:**

None

**Additional Information:**

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
n-Hexane	20 - 30	110-54-3	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Repr. 2; H361 Skin Irrit. 2; H315 STOT SE 3; H336 STOT RE 2; H373
Petroleum distillates	30 - 40	Trade Secret	Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304 Flam. Liq. 4; H227 Aquatic Acute 2; H401 Aquatic Chronic 2; H411
Propane	10 - 20	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Butane	10 - 20	106-97-8	Flam. Gas 1; H220 Liquefied gas; H280
Silicone fluid	5 - 20	Trade Secret	Not classified as dangerous for supply/use.

**Additional Information – None**

\* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES



### Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact

Wash affected skin with soap and water. If symptoms develop, obtain medical attention. Take off contaminated clothing and wash it before reuse. Get medical advice/attention if you feel unwell.

Eye Contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

**Most important symptoms and effects, both acute and delayed**

May be harmful if swallowed and enters airways.

**Indication of any immediate medical attention and special treatment needed**

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Page: 2/7



# OSBORN SILICONE 76241

## SECTION 5: FIRE-FIGHTING MEASURES

### Extinguishing Media

- Suitable Extinguishing Media
- Unsuitable Extinguishing Media

Extinguish with carbon dioxide, dry chemical, foam or water spray.  
Do not use water jet.

### Special hazards arising from the substance or mixture

Pressurised container: May burst if heated

### Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

Eliminate sources of ignition. Avoid contact with skin and eyes. Avoid breathing spray. Wear protective gloves/eye protection.

### Environmental precautions

Prevent release to the environment.

### Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

### Reference to other sections

None

### Additional Information

None

## SECTION 7: HANDLING AND STORAGE

### Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Avoid breathing vapors.

### Conditions for safe storage, including any incompatibilities

- Storage temperature

Keep in a cool, well ventilated place. Store at temperatures not exceeding 50 °C / 122 °F.

- Incompatible materials

This product should be stored away from sources of strong heat or oxidizing chemicals.

### Specific end use(s)

Lubricant

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Limits

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Alkanes and cycloalkanes, C5 - C8	-----	-----	1500 mg/m3	-----	-----	-----
Alkanes & Cycloalkanes, C9-C15	-----	-----	1200 mg/m3	-----	-----	-----
n-Butane	106-97-8	-----	250 ppm	-----	-----	-----
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#
n-Hexane	110-54-3	500 ppm	50 ppm*	-----	-----	*Skin

#Assure minimum oxygen content of work atmosphere; ^NIC = Notice of Intended Changes (ACGIH®)

### Recommended monitoring method

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1550 (Naphthas)

### Exposure controls

## Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

## Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely. Check with protective equipment manufacturer's data.

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

## Environmental Exposure Controls

None known

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Aerosol spray
Color	Colorless
Odor	Petroleum spirit
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Extremely flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. $95 \times 10^4$ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity	<20 cSt @ 40 °C
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Other information	Not available

## SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidizing agents



# OSBORN SILICONE 76241

Hazardous decomposition product(s)

Carbon monoxide, Carbon dioxide, Acid smoke

## SECTION 11: TOXICOLOGICAL INFORMATION

**Exposure routes:** Inhalation, Skin Contact, Eye Contact

### Information on toxicological effects

n-Hexane (CAS No. 110-54-3):

#### Acute toxicity

Oral: LD50 ≈ 16 g/kg-bw (May be fatal if swallowed and enters airways.)

Dermal: LD50 > 2 g/kg-bw. rabbit

Inhalation: LC50 > 17600 mg/m<sup>3</sup> (Vapor), 24-hr. rat (May cause drowsiness or dizziness.)

#### Irritation/Corrosivity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

#### Sensitization

It is not a skin sensitizer.

#### Repeated dose toxicity

LOAEL: 37973 mg/kg (101 days, oral, rat, CNS effects)

NOAEL: 1135 mg/kg (101 days, oral, rat, CNS effects)

NOAEC: 1760 mg/m<sup>3</sup> (90 day, inhal., female mice, nasal lesions)

LOAEC: 3000 ppm (12 hr a day for 16 weeks, inhal., rat, CNS effects)

#### Carcinogenicity (By analogy with similar materials)

NOEL: 31736 mg/m<sup>3</sup> (2 years, inhal. Oncogenic effects)

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

#### Mutagenicity

There is no evidence of mutagenic potential.

#### Reproductive toxicity

Studies in animals have shown that repeated exposures produce adverse reproductive effects.

Propane (CAS# 74-98-6):

#### Acute toxicity

Inhalation: LC50 = 1237 mg/L (2-hr, mouse, gas)

#### Irritation/Corrosivity

No evidence of irritant effects from normal handling and use.

#### Sensitisation

It is not a skin sensitiser.

#### Repeated dose toxicity

NOAEC: ≥ 19678 mg/m<sup>3</sup> (28-day, rat, Systemic effects)

LOAEC: 21641 mg/m<sup>3</sup> (28-day, rat, effects: Body weight)

#### Carcinogenicity

No data. It is unlikely to present a carcinogenic hazard to man.

#### Mutagenicity

There is no evidence of mutagenic potential.

#### Reproductive toxicity

None anticipated

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

#### Acute toxicity (calculated / estimated)

Oral: LD50 > 5000 mg/kg-bw

Dermal: LD50 > 2000 mg/kg-bw

Inhalation: LC0 ≥ 5.28 mg/l (Vapor), 4-hr. rat - May cause drowsiness or dizziness.

#### Irritation/Corrosivity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

#### Sensitization

It is not a skin sensitizer.

#### Repeated dose toxicity

Oral: NOEL 750 mg/kg

Dermal: NOEL 0.5 ml/kg bw

Inhalation: NOEL ≥ 1000 mg/m<sup>3</sup>

#### Carcinogenicity

It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.



# OSBORN SILICONE 76241

Mutagenicity  
Reproductive toxicity

Not to be expected  
Not to be expected

## SECTION 12: ECOLOGICAL INFORMATION

### Ecotoxicity

n-Hexane (CAS# 110-54-3):

Short term

LC50 (96 hour): >1000 µg/L (*Oryzias latipes*)  
LC50 (48 hour): 45 mmol/m3 (*Daphnia magna*, mortality)  
EC50 (96 hour): 2.66% (*C. pyreniodosa*)

Long Term

NOELR (28 days) 2.8 mg/l (*Fish*) QSAR  
NOELR (21 days): 4.88 mg/l (*Daphnia magna*) QSAR  
NOEL (96 hour) 2.077 mg/l (Algae) QSAR

**Persistence and degradability**

Readily biodegradable.

**Bioaccumulative potential**

The product has no potential for bioaccumulation.

**Mobility in soil**

Not available

**Results of PBT and vPvB assessment**

Not classified as PBT or vPvB.

**Other adverse effects**

None known.

Hydrotreated Light Distillate (CAS No. 64742-47-8) - By analogy with similar materials:

Short term

LC50 (96 hour): 2.5 mg/L (fish)  
EC50 (48 hour): 1.4 mg/L (crustacea)  
EC50 (72 hour): 1.3 mg/L (algae)

Long Term

NOEC (28 days): 0.098 mg/L (fish)  
LOEC (21 days): 1.2 mg/L (crustacea)  
LOEL (72 hour): 1 mg/L (algae)

**Persistence and degradability**

Biodegradable

**Bioaccumulative potential**

The product has no potential for bioaccumulation.

**Mobility in soil**

Not available.

**Results of PBT and vPvB assessment**

Not classified as PBT or vPvB.

**Other adverse effects**

None known.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste treatment methods**

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

## SECTION 14: TRANSPORT INFORMATION

	U.S. DOT	Sea transport (IMDG)	Air transport (ICAO/IATA)
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable



# OSBORN SILICONE 76241

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
n-Hexane	110-54-3	52	5000

SARA 311/312 - Hazard Categories:

☒ Fire ☒ Sudden Release ☐ Reactivity ☒ Immediate (acute) ☒ Chronic (delayed)

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
n-Hexane	110-54-3	25 - 30

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None	-----	-----

## SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: May 19, 2015

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H225: Highly flammable liquid and vapor.
- H227: Combustible liquid.
- H280: Contains gas under pressure; may explode if heated.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H336: May cause drowsiness or dizziness.
- H361: Suspected of damaging fertility or the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure:
- H401: Toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.